TRADITIONAL BULB

SERIE 5000 REEL + T306 LAMP

NO TRANSFORMER



CABLE LENGTH: 15,5 m (14+1,5)
INCOMING CABLE: 1 m
CABLE TYPE: H05 RN-F - 2x1 mm²
REEL PROTECTION DEGREE: IP42

ENG LAMP FEATURES

· Insulated handgrip made of oil, acid, solvent-resistant Moplen.
· Reflecting cage made of zinc-coated steel.
· Recessed lever switch.
· Rotating hanging-hook.

FRA CARACTERISTIQUES DE LA BALADEUSE


· Poignée anatomique en Moplen, anti-acide, anti-solvant.
· Cage en fil d'acier à charnière et réflecteur en tôle d'acier zingué.
· Interrupteur robuste emboité et protégé.
· Crochet pivotant.

GER LAMPENEIGENSCHAFTEN

· Anatomisch geformter Handgriff aus öl-, säure und lösemittelbeständigem Kunststoff.
· Scharnierkäfig aus Stahldraht und Reflektor aus galvanisiertem Stahlblech.
· Im Griff eingelassener geschützter Schalter.
· Drehbarer Aufhängehaken.

ESP CARACTERISTICAS DE LA LAMPARA

· Mango con forma anatómica de plástico anti-aceite, antiácido y anti-disolvente.
· Jaula de hilo de acero a cremallera y reflector en chapa de acero galvanizado.
· Interruptor protegido en un hueco encastrado.
· Gancho giratorio.

ART.	5907/T306
Description	Cable reel with lamp T306
cable length	15,5 m (14 + 1,5)
bulb type and power	not included Max 60W E27
lamp protection degree	IP20
supply voltage	Max 250V
	60
	mm 390x310x165 Kg 4,5

YES
TRANSFORMER

TRADITIONAL BULB

SERIE 5000 REEL + T306 LAMP + TRANSFO

CABLE LENGTH: 15,5 m (14+1,5)
INCOMING CABLE: 1 m
CABLE TYPE: H05 RN-F - 2x1 mm²
REEL PROTECTION DEGREE: IP42



ENG The model with transformer allows to have the lamp feeded at low voltage (12V / 24V), as requested by the safety rules.

FRA Le modèle avec transformateur permet d'avoir la baladeuse alimentée à basse tension (12V / 24V), comme prévu par les normes de sécurité.

GER Das Model mit Trafo erlaubt die Lampe mit Niederspannung (12V / 24V) gemäß den Sicherheitsnormen zu versorgen.

ESP El modelo con transformador permite de alimentar la lampara en baja tension (12V / 24V) ségun las normas de Seguridad.

ART.	5908/T306
Description	Cable reel with transfo + lamp T306
cable length	15,5 m (14 + 1,5)
transfo features	power: 63VA input: 230V output: 12V and 24V
bulb type and power	not included Max 60W E27
lamp protection degree	IP20
supply voltage	230V
	44
1	mm 345x305x230 Kg 6,0



DIMENSIONS

