> Avviatori d'emergenza SERIE CLASSIC
> *Portable boosters CLASSIC SERIES*

F3000

Cod. 03.015.00
F3000 12V

12V-22Ah | 2000A PEAK | CBA 150 | DOUBLE

HAPPY VAN

Cod. 03.016.00
HAPPY VAN 12V

GENESIS 12V-26Ah | 2500A PEAK | CBA 400 | DOUBLE | BATTERY BREAKER

F4000

Cod. 03.015.01
F4000 12-24V

12-24Ah 2X22Ah | 4000A 2000A PEAK | CBA 400 | DOUBLE

HAPPY TIR

Cod. 03.018.01
HAPPY TIR NEW 12-24V

GENESIS 12-24Ah 2X22Ah | 4000A 2000A PEAK | CBA 1200 | DOUBLE

Cod. 05.088.03
>Carrello per New Happy Tir
>Trolley for New Happy Tir

HAPPY TANK

Cod. 03.019.01
HAPPY TANK PLUS 12-24V

OPTIMA 12-24Ah 2X54Ah | 6400A 3200A PEAK | CBA 1200 | DOUBLE

Corredo standard/Standard outfits

Cod. 03.022.01
CBA 150N
>Carica batterie automatico. 1,5A 12V **(per F3000).**
>Automatic battery charger. 1,5A 12V **(for F3000)**

Cod. 03.024.09
CBA 400
>Carica batterie automatico. 4A 12V **(per F4000, Happy Van).**
>Automatic battery charger. 4A 12V **(for F4000, Happy Van)**

Cod. 03.024.06
CBA 1200
>Carica batterie automatico. 12A 14V **(per New Happy Tir, Happy Tank Plus)**
>Automatic battery charger. 12A 14V **(per New Happy Tir, Happy Tank Plus)**

> Avviatori d'emergenza SERIE EVOLUTION
> *Portable boosters EVOLUTION SERIES*

Cod. 03.015.03
BOCIA EVO 12V

12V 2X22Ah | 2000A PEAK | 1A-12V | DOUBLE | BATTERY BREAKER | LAMP

Cod. 03.015.04
BOCIA EVO 12-24V

12-24Ah 2X22Ah | 4000A 2000A PEAK | 4A-12V | DOUBLE | BATTERY BREAKER | LAMP

Cod. 03.016.01
HAPPY VAN EVO

12V 2X22Ah | 4000A PEAK | 4A-12V | DOUBLE | BATTERY BREAKER | LAMP

- Nuova impugnatura ergonomica in gomma
- Stacca batteria di serie (+ buzzer)
- Luce a led di emergenza

(Modelli Bocia Evo 12-24V e Happy Van Evo)

- New ergonomic rubber handle
- Standard battery switch (+buzzer)
- Luce a led di emergenza

(Bocia Evo 12-24V & Happy Van Evo models)

> Caricabatterie-alimentatori LINEA CHARGEMATE
> *Battery Charger & Power Supply CHARGEMATE LINE*

Cod. 03.024.17
CHARGEMATE 12-24V/100A

Cod. 03.024.18
CHARGEMATE 12-24V/50A

Ricaricano tutti i tipi di batterie automotive e industriali con tecnologia a inverter e differenti curve di carica. Funzione alimentatore a tampone per riprogrammazione centraline elettroniche

- Corrente di carica: 3÷50 o 100A DC
- Capacità batterie: 30/1200 Ah
- Tensione di alimentazione: 220-240V
- Tensione di carica: 12/24V
- Dimensioni: 29x34x13
- Peso: 5kgs

Charger with inverter technology that works as buffer power supplier for systems equipped with electrical control units. Ideal for use in the automotive and industrial field.

- Charge current: 3÷50 or 100A DC
- Batteries' capacity: 30/1200Ah
- Supply tension: 220-240V
- Charge tension: 12/24V
- Dimensions: 29x34x13
- Weight: 5kgs

> Avviatori d'emergenza con batterie al litio/cobalto
> *Power Pack with Lithium / Cobalt batteries*

Cod. 03.020.01
POWER PACK 16000

NEW!

- Capacità batteria: 16 000mAh
- 400A (Peak) 12 V per l'avviamento
- Uscite 5V/0.1÷2A per i cellulari, tablet, notebook etc.
- Caricatore 12V presa accendisigari / 220 V da presa
- Tempo di ricarica: 4-5h
- 4 led indicazione carica
- Protezione contro inversioni di polarità (Jump Start)
- Dimensioni e peso: 165x79x40mm; 460g

- Battery capacity: 16000mAh
- Peak current: 400 A 12 V
- Output 5V/0.1÷2A for charging of phones, tablets, laptops etc.
- 12 V (cigarette lighter socket) / 220 V charger
- Full charging time: 4-5h
- 4 LED charge indication
- Reverse polarity protection (Jump Start function)
- Dimensions and weight: 165x79x40mm; 460g

Cod. 03.020.02
POWER PACK TRUCK

NEW!

- Capacità batteria: 30.000mAh
- Uscite a 5V/1A, 5V/2.1A,12V/10A,12÷24V in avviamento
- Ricarica: 14V/1A
- Tempo di ricarica: 10h
- Corrente di avviamento (a freddo): 12V/300A; 24V/400A
- Corrente di picco: 800A
- Protezioni: corto circuito,sovraccarico e sottoscarica
- Dimensioni e peso: 200x164x90mm; 1500g

- Battery capacity: 30.000mAh
- Output: 5V/1A, 5V/2.1A, 12V/10A, 12÷24V jump start
- Input: 14V/1A
- Full charging time: 10h
- Starting current (cold): 12V/300A; 24V/400A
- Peak current: 12V/400A; 24V/800A
- Protections: short circuit, overcharge, low charge
- Dimensions and weight: 200x164x90mm; 1500g