EURARC 522 230V/400V

Overview

EURARC 522 230V/400V
cod. 817018
MMA stick electrode welding machine in alternating current (AC). Stepless regulation of welding current. With thermostatic protection. The model has double secondary voltage for use also with basic and rutile electrodes.

- MMA 2AC
- 1 PH 230V
- 2 PH 400V
- CE MARKING
- EAC CERTIFICATION
- TÜV CERTIFICATION

Technical data

- CODE 817018
- MAINS VOLTAGE 230 V - 1 ph 50/60Hz
- MAINS VOLTAGE 400 V - 2 ph 50/60Hz
- CURRENT RANGE 40 - 400 A AC
- MAX CURRENT (EN 60974-1) 350 A - 35 % AC
- CURRENT AT 60% (EN 60974-1) 265 A AC
- MAX NO LOAD VOLTAGE 52 - 71 V AC
- ABSORBED POWER AT 60% - MAX 11 - 15 kW
- POWER FACTOR (cosphi) 0,7
- D. USABLE ELECTRODES IN AC 1,6 - 6 mm
- PROTECTION DEGREE IP22
- DIMENSIONS 95 - 49 - 68 cm
- WEIGHT 81 kg
- EAN CODE 800489785092 4
- PIECES/PALLET 6 pz/pallet
- PIECES/PALLET - B 3 pz/pallet - B