LINEAR 280 230-400V

Aluminium

Overview

LINEAR 280 230-400V
cod. 818002
MMA, rectified, electrode welding machine in direct current (DC). Stepless regulation of welding current. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.

- MMA DC
- RECTIFIED
- 3 PH 230V-400V
- CE MARKING
- EAC CERTIFICATION
- TÜV CERTIFICATION

Technical data

- CODE 818002
- MAINS VOLTAGE 230 / 400 V - 3 ph 50/60Hz
- CURRENT RANGE 50 - 260 A DC
- MAX ABSORBED CURRENT 230 A - 25 % DC
- MAX CURRENT (EN 60974-1) 190 A - 35 % DC
- CURRENT AT 60% (EN 60974-1) 140 A DC
- MAX NO LOAD VOLTAGE 62 V DC
- ABSORBED POWER AT 60% - MAX 5 - 8 kW
- POWER FACTOR (cosphi) 0,6
- D. USABLE ELECTRODES IN DC 1,6 - 5 mm
- PROTECTION DEGREE IP22
- DIMENSIONS 89 - 46 - 59 cm
- WEIGHT 65 kg
- EAN CODE 800489731251 4
- PIECES/PALLET 6 pz/pallet
- PIECES/PALLET - B 3 pz/pallet - B