LINEAR 530 HD 230-400V

CARBON CUT

Aluminium

Overview

LINEAR 530 HD 230-400V
cod. 819055
MMA, rectified, electrode welding machine in direct current (DC). Stepless regulation of welding current. Use with a wide range of electrodes: rutile, basic, stainless steel, cast iron and aluminium.

- MMA DC — MMA DC
- RECTIFIED — RECTIFIED
- 3 230/400V — 3 PH 230V-400V
- CE — CE MARKING
- EAC — EAC CERTIFICATION
- TÜV — TÜV CERTIFICATION

Technical data

- CODE — CODE 819055
- V PH — MAINS VOLTAGE 230 / 400 V - 3 ph 50/60Hz
- A MIN MAX — CURRENT RANGE 60 - 450 A DC
- A MAX 40°C — MAX CURRENT (EN 60974-1) 410 A - 45 % DC
- A 60% 40°C — CURRENT AT 60% (EN 60974-1) 350 A DC
- V0 — MAX NO LOAD VOLTAGE 70 V DC
- P 60% MAX — ABSORBED POWER AT 60% - MAX 16 - 20 kW
- φ — POWER FACTOR (cosphi) 0,7
- Ø DC MIN/MAX — D. USABLE ELECTRODES IN DC 2 - 8 mm
- IP — PROTECTION DEGREE IP22
- W H L — DIMENSIONS 100 - 54 - 76 cm
- kg — WEIGHT 170 kg
- BAR CODE — EAN CODE 800489777861 7
- PIECES/PALLET 3 pz/pallet