SUPERIOR 630CE VRD MIG PACK AQUA230-400V

EMF SAFE | MMA | MIG MAG | TIG

4 ROLLS | VRD VOLTAGE REDUCTION DEVICE | CARBON CUT | Cellulosic | STEEL STAINLESS STEELS

Overview

SUPERIOR 630CE VRD MIG PACK AQUA230-400V
cod. 816044
High power MIG-MAG/FLUX/MMA/TIG multi-process inverter generator suitable for heavy duty use on worksites and industrial environments. MIG-MAG/TIG welding of all types of steels and steel by-products and MMA welding of all types of electrodes up to 8 mm in diameter. The optional removable wire feeder and connection cables make it possible to increase the field of intervention. Compactness and easy transport features guarantee high levels of mobility and flexibility of use. Complete with wirefeeder, MIG-MAG welding accessories, trolley and water cooling unit GRA 3000.

- MMA TIG DC - LIFT
- MIG-MAG FLUX
- 3 PH 400V
- FAN COOLED
- EXTENSIONS MAX 30 m
- MICROPROCESSOR
- REMOTE CONTROLS
- COIL 15 kg
- CE MARKING
- EAC CERTIFICATION

Technical data

- CODE 816044
- MAINS VOLTAGE 230 / 400 V - 3 ph 50/60Hz
- CURRENT RANGE 10 - 450 / 10 - 600 A DC
- MAX CURRENT (EN 60974-1) 400 A - 35 % / 500 - 40 % DC
- CURRENT AT 60% (EN 60974-1) 300 / 400 A DC
- MAX NO LOAD VOLTAGE 65 / 73 V

SUPERIOR 630CE VRD MIG PACK AQUA230-400V

ABSORBED CURRENT AT 60% - MAX 25 / 20 - 44 / 35 A

ABSORBED POWER AT 60% - MAX 10 / 13 - 16 / 23 kW

EFFICIENCY 86 %

STEEL WELDING WIRE DIAMETER 0,6 - 2,4 mm

INOX WELDING WIRE DIAMETER 0,8 - 2,4 mm

ALUMINIUM WELDING WIRE DIAM. 0,8 - 1,6 mm

FLUX CORED WELDING WIRE DIAM. 1 - 1,2 mm

BRAZING WIRE DIAM. 0,8 - 1,2 mm

D. USABLE ELECTRODES IN DC 1,6 - 8 mm

PROTECTION DEGREE IP23

DIMENSIONS 95 - 45 - 145 cm

WEIGHT 108 kg

EAN CODE 800489794839 3

Included Accessories

CABLE 70MMQ 3M-WORK CLAMP-DX 70 - 723032

TORCH HOOK - 644444

MT500 MIG TORCH 3 M AQUA - 722625