AUTOTRONIC 25 BOOST 230V 12V/24V

Tronic | 12V | 24V | Pb-Ca

Wet | Gel | AGM | EFB | MF

Overview

AUTOTRONIC 25 BOOST 230V 12V/24V
cod. 807540
Battery charger with electronic control of the charging current, automatic interruption and restart (TRONIC), for charging lead-acid batteries with 12/24V voltage.
Fit with switches to choose either anormal charge (MIN) or quick charge (BOOST) in the buffer mode (TRONIC) or drooping characteristic mode (CHARGE).
The buffer automatic charge is adequate for maintenance free sealed batteries (GEL/AGM/START-STOP), while the drooping characteristic charge is adequate for free-electrolyte batteries (WET).
Characteristics:
* choice of output voltage, type of charge, charging mode
* display of charging current
* protection against overloads and polarity reversal.

- 1 PH 230V
- CAR
- BOAT
- TRACTOR
- VAN
- CE MARKING
- EAC CERTIFICATION
- TÜV SUD CERTIFICATION

Technical data

- CODE 807540
- MAINS VOLTAGE 230 V - 1 ph 50/60Hz
- CHARGING ABSORBED POWER 300 W

AUTOTRONIC 25 BOOST 230V 12V/24V

- CHARGING VOLTAGE 12 / 24 V
- EFFECTIVE CHARGING CURRENT 18 / 12 A
- RATED CHARGE CURR. EN60335-2-29 12 / 8 A
- MIN./MAX RATED REFERENCE CAPACITY 30/225 - 12V Ah
- MIN./MAX RATED REFERENCE CAPACITY 20/180 - 24V Ah
- ADJUSTMENT POSITIONS 4
- DIMENSIONS 22,5 - 29 - 20,5 cm
- WEIGHT 7,2 kg
- EAN CODE 800489764142 3
- PIECES/PALLET 56 pz/pallet
- PIECES/PALLET - B 42 pz/pallet - B

Included Accessories

- COLORADO 40B WORK CLAMP 40A - 712624
- COLORADO 40R POSITIVE CLAMP 40A - 712623
- POSITIVE CABLE 2,5 MMQ 1,5 M - 123986
- WORK CABLE 2,5 MMQ 1,5 M - 123985